

# FLOS

09.8301.DY Matte White

## Oblique

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 482lm - 3000K - CRI> 90 - Beam° 34

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Driver input: 24 V

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Table               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 8                   |
| System power (W)       | 18                  |
| Source flux (lm)       | 760                 |
| Lumen Output (lm)      | 482                 |

### Physical

|                 |             |
|-----------------|-------------|
| Colour          | Matte White |
| Orientation     | Fixed       |
| Net weight (kg) | 0.75        |
| IP internal     | 20          |
| IP external     | 20          |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP

### Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Photometric

|                                 |                               |
|---------------------------------|-------------------------------|
| Lighting type                   | Direct                        |
| Light distribution              | Asymmetric                    |
| CCT (K)                         | 3000                          |
| CRI>                            | 90                            |
| LED Life / Failure Ratio        | L90B10 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)           | 34                            |
| Beam angle indirect C0-180 (°)  | 35                            |
| Beam angle indirect C90-270 (°) | 46                            |

Electrical

|                           |                 |
|---------------------------|-----------------|
| Insulation class          | III             |
| Power supply              | Remote included |
| Dimmable                  | Yes             |
| Power supply type         | Dimmable        |
| Emergency                 | No              |
| Induction recharge QI     | No              |
| Charging socket/connector | USB-C           |